

**Key Features & Benefits:**

**Installation**

- Strong spring clips to secure housing to drywall ceiling tiles & downlight mounting plate

**Ratings**

- Acceptable for use in IC or Non-IC applications
- Wet Location rated
- Energy Star listed

**Construction**

- Recessed bevel for smooth, even, optimal light distribution
- Cast Aluminum housing and trim

Rated Lifetime\_L70 >50,000 hrs

Dimmable to 10% (120V) Triac

Project: \_\_\_\_\_


Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_

**9 LIGHTS IN ONE**

**SELECTABLE KELVIN**



**SELECTABLE WATTAGE**



**Product Specifications:**

- Selectable Wattage: 10/15/22 Watts
- Lumens: Up to 1,950 Lumens
- Input Voltage: 110–277 VAC
- Power Factor: >0.98
- CRI: 90+
- Selectable Kelvin: 3000K, 4000K, 5000K
- Input Frequency: 50/60Hz
- Operating Temperature: -13°F to 114°F (-25°C to 45°C)
- Max Mounting Thickness: 5"



### Ordering Guide:

ESL	TYPE	SIZE	SELECTABLE WATTAGE	GENERATION	SELECTABLE KELVIN	DIMMING
ESL	OPT (OPT) Optus Series	6 (6) Round 5/6" (8) Round 8"	XW 6": 10–15–22 Watts 8": 12–20–30 Watts	1 (1) 1st Generation	YY (YY) 3000K–4000K–5000K	10V (10V) 1–10V Dimming

### FACTORY INSTALLED OPTIONS

EM9	Emergency Backup Battery unit w/ Auto Test function, 9 Watts output, 90 minutes minimum, 120–277 VAC Input, 10–300 VDC output, closed frame with dual flex conduits, UL listed for factory or field install, Title 20
-----	---

### FIELD INSTALLED ACCESSORIES

ESL-EMG-SL1-CDC-9W	Emergency Backup Battery unit w/ Auto Test function, 9 Watts output, 90 minutes minimum, 120–277 VAC Input, 10–300 VDC output, closed frame with dual flex conduits, UL listed for factory or field install, Title 20
ESL-KNX-RPP-002	Konex Power Pack Relay Controller, 120–277 VAC with power statistics
ESL-RDL-4-RKIT-001	4", new construction Rough-In plate
ESL-RDL-6-RKIT-001	6", new construction Rough-In plate
ESL-RDL-8-RKIT-001	8", new construction Rough-In plate

\*ESL-EMG-SL1-CDC-18W (EM18)—18 Watt Emergency Backup works ONLY with the 8" fixture

### Catalog Data:

ITEM#	SELECTABLE WATTAGE	SELECTABLE KELVIN	MAX LUMEN OUTPUT	MAX EFFICACY (lm/W)	INPUT VOLTAGE	DIMENSIONS
<b>5/6" ROUND</b> ESL-OPT-6-XW-1YY-10V	10W–15W–20W	3000K–4000K–5000K	1,950	89	120–277 VAC	Ø8.23" x 3.98"
<b>8" ROUND</b> ESL-OPT-8-XW-1YY-10V	12W–20W–30W	3000K–4000K–5000K	2,350	77	120–277 VAC	Ø10.24" x 4.41"

### Dimensions:

