HellermannTyton

Specification Sheet

Part Number: 181-92004



| Article Number | 181-92004 |
|---------------------|---|
| Туре | TC2 |
| Color | Gray (GY) |
| Features & Benefits | • A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. • Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement. • Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately) |
| Quantity Per | box |
| Product Description | HellermannTyton's Pro-Duct wiring duct covers are sold separately and interchangeable among the 3 styles of duct (solid, slotted and high density). Manufactured from high impact, rigid PVC, Pro-Duct covers come in standard colors of white, gray and black. Wiring duct covers are available in 6 foot lengths. |

| Short Description | Wiring Duct Cover for 2" Duct, 6 ft Long, PVC, Gray, 30ft/box |
|--------------------------------|---|
| Global Part Name | TC2-PVC-GY |
| Technical Description | Wiring Duct Cover for 2" Duct, Gray |
| | |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 1.83 |
| Width W (Imperial) | 2.0 |
| Width W (Metric) | 50.8 |
| Height H (Imperial) | 0.308 |
| Height H (Metric) | 7.82 |
| | |
| | |
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |
| Flammability | Self-Extinguishing |
| Halogen free | No |
| Operating Temperature (Metric) | +122°F (+50°C) |
| Reach Complaint(Article 33) | No |

| ROHS Complaint | Yes |
|---------------------------------|--|
| Certification/Specification WEB | UL EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A CSA |
| UL Recognized (US) | Yes |
| | |
| Package Quantity(Imperial) | 30 |
| Package Quantity (Metric) | 9.14 |
| Customs Number | 3925900000 |

 $\ensuremath{\mathbb{C}}$ 2018 HellermannTyton. All rights reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions