

**date** 03/07/2012

page 1 of 3

## SERIES: MD-XXSV | DESCRIPTION: MINI DIN CONNECTOR


#### **FEATURES**

- PCB mount
- vertical mount
- 3~8 pins





### **PART NUMBER KEY**




### **SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated input voltage			100 12		Vac Vdc
rated input current	at 100 Vac at 12 Vdc			1 2	A A
contact resistance				30	mΩ
insulation resistance	at 250 Vdc	50			МΩ
voltage withstand	for 1 minute			250	Vac
insertion force		1		4.5	kg
withdrawl force		0.8		3	kg
operating temperature		-40		85	°C
life			1,000		cycles


## **MECHANICAL DRAWINGS**


units: mm[inches]


TOLERANCE: ±0.2mm



	MATERIAL	PLATING
earth terminal	brass	tin
contact terminals (1~8)	phosphor bronze	silver
plastic	PBT	









# MD-60SV





#### MD-80SV





#### **REVISION HISTORY**

rev.	description	date	
1.0	initial release	02/23/2006	
1.01	new template applied	03/07/2012	

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters 20050 SW 112th Ave. Tualatin, OR 97062 800.275.4899

Fax 503.612.2383 cui.com techsupport@cui.com

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.