
KEMET Part Number: PMR209MC6100M047R30

(P409CE104M250AH470)



Capacitor, Film, Metallized Paper, 0.1 uF, +/-20% Tol, -40/+85C, Integrated Resistor (X2), 630 VDC@85C, Lead Spacing=20.3 mm, Not For New Design, Please Check Possible Alternative Parts (AltPart)



| Dimensions (mm) | | | |
|-----------------|-----------|-----------|--|
| Symbol | Dimension | Tolerance | |
| L | 24 | MAX | |
| Н | 14 | MAX | |
| Т | 7.6 | MAX | |
| S | 20.3 | +/-0.4 | |
| LL | 30 | +5 | |
| F | 0.8 | +/-0.05 | |

| Packaging Specifications | | |
|--------------------------|------|--|
| Package Kind: | Bulk | |
| Package Quantity: | 250 | |

| General Information | | |
|---------------------|--------------------------|--|
| Supplier: | KEMET | |
| Dielectric: | Metallized Paper | |
| Application: | Integrated Resistor (X2) | |
| Style: | Radial Molded | |
| Lead Form: | Wire Leads | |
| Features: | Pulse | |
| RoHS: | Yes | |

| Specifications | | |
|------------------------|---|--|
| Capacitance: | 0.1 uF | |
| Voltage: | 630 VDC | |
| Tolerance: | +/-20% | |
| Voltage AC: | 250 VAC | |
| Rated Temperature: | 85C | |
| Temperature Range: | -40/+85C | |
| Insulation Resistance: | 3 GOhm | |
| Miscellaneous: | Not For New Design, Please Check Possible Alternative Parts (AltPart) | |
| Miscellaneous: | Resistor= 47 Ohms | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

